



Air Conditioning & Heating

- [Home](#)
- [About Goodman](#)
- [Product Information](#)
- [Heating & Cooling 101](#)
- [Locate a Dealer](#)
- [Warranty](#)
- [Employment](#)



Home > Product Information > Product Specifications

## GSC13 Series 13 SEER 1½ to 5 Ton



The Goodman® GSC13 13 SEER Air Conditioner features the unique Goodman® sound control top design for quiet operation. In addition, the unit has an attractive louvered metal guard that protects the coil from damage plus a powder-paint finish that provides premium durability and improved UV protection.

### Standard Features

- Energy-efficiency compressor
- Copper tube/aluminum fin coil
- 850 RPM condenser fan motor
- R-22 refrigerant-charged for 15' of refrigerant lines
- Factory-installed liquid line filter dryer
- Brass liquid and suction service valves with sweat connections
- Contactor with lug connections
- Ground lug connection
- ETL Certified

### Cabinet Features

- Unique Goodman® sound control top design
- Steel louver coil guard
- Heavy-gauge galvanized-steel cabinet
- Attractive Architectural Gray powder-paint finish with 500-hour salt-spray approval
- When properly anchored, meets the 2001 Florida Building Code unit integrity requirements for hurricane-type winds

### Split System Air Conditioners

- 14 SEER GSC14 :
- 14 SEER CLQ Series :
- 13 SEER GSC13 :**
- 13 SEER CLT Series :
- 13 SEER CRT Series :
- CKL Commercial :

[Split System Heat Pumps](#)

[Gas Furnaces](#)

[Air Handlers](#)

[Packaged Air Conditioners](#)

[Packaged Heat Pumps](#)

[Packaged Gas/Electric](#)

[Coils](#)

[Indoor Air Quality](#)

[Quietflex - Flex Duct](#)

[Export Products](#)

[Product / Warranty Registration](#)

[Financing](#)

[What is EnergyStar?](#)

[Federal Tax Credits](#)



[Printer Friendly Version](#)

[Product Brochure](#)

[Product Specifications](#)

[Product Warranty](#)

Model	Nominal Cooling Capacity (BTU/h)	Voltage-Phase	MOD* (amps)	Dimensions W x D x H	Service Valve		dBs	Ship Weight (lbs)
					Liquid	Suction		
GSC130181AA	18,000	208/230-1	15	26 x 26 x 29¾"	¾"	¾"	78	173
GSC130241A	24,000	208/230-1	15	26 x 26 x 34¾"	¾"	¾"	78	195
GSC130241C	24,000	208/230-1	20	26 x 26 x 34¾"	¾"	¾"	78	182
GSC130301A	30,000	208/230-1	20	26 x 26 x 34¾"	¾"	¾"	78	195
GSC130301B	30,000	208/230-1	20	29 x 29 x 34¾"	¾"	¾"	78	195
GSC130361AA	36,000	208/230-1	20	29 x 29 x 34¾"	¾"	¾"	80	199
GSC130361BA	36,000	208/230-1	30	29 x 29 x 34¾"	¾"	¾"	80	205
GSC130361CA	36,000	208/230-1	30	29 x 29 x 34¾"	¾"	¾"	80	214
GSC130363A	36,000	208/230-3	20	29 x 29 x 34¾"	¾"	¾"	80	198
GSC130421AA	42,000	208/230-1	30	29 x 29 x 34¾"	¾"	¾"	76	199
GSC130481AA	48,000	208/230-1	40	29 x 29 x 38¾"	¾"	¾"	76	207
GSC130483A	48,000	208/230-3	20	29 x 29 x 38¾"	¾"	¾"	76	207

GSC130484AA	48,000	460-3	15	29 x 29 x 38¼	¾"	7/8"	76	207
GSC130601B	57,000	208/230-1	50	35½ x 35½ x 38¼	¾"	7/8"	77	242
GSC130603A	57,000	208/230-3	40	35½ x 35½ x 38¼	¾"	7/8"	77	242
GSC130604A	57,000	460-3	15	35½ x 35½ x 38¼	¾"	7/8"	77	242

\* Maximum Overcurrent Protection Device

[PartnerLink](#)  
Policy

[Contact Us](#)

[Site Map](#)

[Privacy](#)

Copyright © 2003-2006 Goodman Manufacturing Company, L.P. All Rights Reserved.

Duplication in part or in whole is strictly prohibited.